

Product description

Bono 5530 is a double sided XPE foam tape for mounting applications. Generally, widely used in Automotive Parts & Hardware mounting, leather, nameplate, stationery, electronics, fixing, footwear, paper making, handicraft paste positioning and other purposes.

Product Information	
Material of Carrier	XPE Foam
Density of Foam	100 g/m ³
Color of Carrier	white
Total thickness	1150 µm
Type of adhesive	Acrylic PSA
Material of Liner	silicon coated paper
Color of Liner	Havana
Thickness of Liner	80 µm
Weight of liner	90 g/m ³

Technical Information (average values)		
Adhesion to Steel (after 30 min)	8N/25mm	PSTC-101 / ASTM D 3330
Adhesion to Steel (after 24h)	20N/25mm	PSTC-101 / ASTM D 3330
Initial Tack	12#	GB/T 4852-2002
Tensile Strength	20N/25mm	PSTC-131 / ASTM D 3759
Elongation	100%.	PSTC-131 / ASTM D 3759
Service Temperature	-10~ +100 °C	-----

Product Form and Size

Cut Roll: 10/ 20 / 30 / 40/ 50 mm (standard) or custom-cut dimensions

Log Roll: 1000mm x25m/1000mm x50m

Important Note

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Thickness: $\pm 100\mu\text{m}$; Width: $\pm 1\text{mm}$; Length: Cut Roll: $\pm 0.1\text{m}$

Storage and Shelf Life

12 months when stored at $25\pm 2\text{ }^{\circ}\text{C}$ / 50% relative humidity out of direct sunlight.

Surface Preparation

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.