Bono 2652

Product description

Bono 2652 is a high-quality tape based on composite materials of polyethylene and gauze fabric as base material. The tape is coated with high viscosity natural rubber adhesive. The characteristics of the tape are: strong stripping, tensile, grease resistance, aging resistance, waterproof, corrosion resistance, etc. Mainly used for bandaging, sealing, heavy binding, fixing and etc.

Product Information	
Material of Carrier	Composite PE fabric
Color of Carrier	Blue, Red, White, Silver, Black
Total thickness	250 μm
Type of adhesive	Natural rubber

Technical Information (average values)		
Initial Tack	≥17#	GB/T 4852-2002
Adhesion to Steel	≥12N/25mm	PSTC-101 / ASTM D 3330
Tensile Strength	≥113N/25mm	PSTC-131 / ASTM D 3759
Elongation	≥10%	PSTC-131 / ASTM D 3759
Applying Temperature	10 ~ 40 ° C	
Service Temperature	-5 ~ 100 ° C	

Important Note

1. The data above are typical values only, and should not be used for specifications purpose.
2. Tolerance: Thickness: ±5μm; Width: ±1mm; Length: Cut Roll: ±0.2m

Storage and Shelf Life

12 months when stored at 23±2 ◦C / 70% relative humidity out of direct sunlight.

Surface Preparation

All the above data and information are based on our test results. Users must determine the applicability of the product for the desired purpose before use.